4º Batalhão de Aviação do Exército
152

WARNING

Dry ice, Item 125, will cause severe frostbite on exposed skin. Avoid contact. Avoid breathing vapor. Prolonged inhalation may cause shortness of breath, nose/throat irritation, watery eyes and headache. Prolonged overexposure may cause coma and death. If solid carbon dioxide contacts skin, immediately flush area with lukewarm water. Do not rub affected area. Seek medical attention. If other symptoms of overexposure appear, seek fresh air and possible medical attention. CAUTION: Do not place solid carbon dioxide in sealed containers; heat will sublime ice to form gas, increasing pressure and resulting in explosion. Do not put head or limbs into dry ice containers. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: goggles or face shield, heavy approved gloves, thick full-body protective clothing.

WARNING

Epoxy coating, Item 126A, is flammable. Keep container closed; keep sparks, flames, and heat away. Bond/ground metal containers during transfer to prevent ignition through static discharge. Keep coating off skin, eyes, and clothes. May irritate the eyes and skin. May contain chemicals that may be absorbed through the skin in dangerous amounts that can affect inner organ systems or that may, upon long-term exposure, damage inner "target" organs. Breathing vapor may cause headache, dizziness, nausea, respiratory irritation. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, gloves, forced ventilation or NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
12 52

WARNING

Epoxy patch kit, Item 134, is a two component product consisting of an epoxy resin Part A and hardener, Part B. The precautions for each should be observed when separate or mixed. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Epoxy Resin, AA0151, Part A: Direct contact with eyes may cause moderate irritation. Skin contact may cause moderate irritation. Inhalation should not be a hazard due to low volatility. Ingestion should not be a hazard due to low order of toxicity. In case of eye contact, flush with water for 15 minutes holding eyes open, obtain medical attention; in case of skin contact, wash with soap and water and obtain medical attention if irritation persists. In case of inhalation remove to fresh air and obtain medical attention; In case of ingestion, do not induce vomiting and obtain medical advice. Protection: safety goggles, approved gloves, good ventilation. Hardener, AB0151, Part B: Product severely irritates the eyes and skin. Permanent impairment of vision or blindness may occur. Ingestion may cause burns to the mouth and upper gastrointestinal tract. Inhaling vapors will cause irritation and sensitization responses in susceptible individuals such as respiratory distress. In case of eye contact, flush with water for 30 minutes while holding lids open and obtain immediate medical attention. In case of skin contact, flush the area with water, remove contaminated clothing and obtain medical attention. In case of inhalation, remove to fresh air and obtain medical attention if symptoms persist. In case of ingestion, do not induce vomiting, give large quantities of water if conscious and obtain immediate medical attention. Protection: safety goggles, approved gloves, good ventilation.

WARNING

Epoxy Primer, Item 135, is flammable. Do not use near open flames, welding areas, or on hot surfaces. Do not eat, drink, or smoke where primers are being mixed, handled, or cleaned up. Prolonged breathing of vapors or spray mist should be avoided. Avoid prolonged skin contact. Contains chromates; follow approved toxic waste disposal procedures. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: respiratory protection.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
1153

WARNING

Etching Solution, Item 136, is flammable. Do not use near open flames, welding areas, or hot surfaces. Bond and ground metal containers during transfer to prevent ignition through static discharge. Keep containers closed when not in use. Dispose of liquid-soaked rags in approved metal container. Avoid contact; contact will cause severe burns to exposed tissue. May be absorbed through the skin in potentially dangerous levels that may affect inner organs. If liquid contacts the eyes or skin, immediately flush the affected area thoroughly with water, and get medical attention. Change contaminated clothing immediately. Avoid breathing vapor. Inhalation may cause fatigue, headache, dizziness, nausea, and upper respiratory irritation. If symptoms appear, seek fresh air and possible medical attention. CAUTION: Reacts with water to form caustic soda. May form explosive peroxide if stored for over six months. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical goggles or face shield, neoprene gloves, full-body protective clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Ethylene Glycol, Item 137, may cause slight eye and skin irritation upon prolonged or repeated contact. Keep container closed; keep sparks, flames, and heat away. Keep ethylene glycol off skin, eyes, and clothes. Breathing vapors or mists of heated or agitated ethylene glycol may cause dizziness and upper respiratory irritation. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles or safety glasses, chemical-resistant gloves, other protective clothing as needed, good ventilation.

WARNING

Grease, Item 143, may cause moderate irritation to eyes. In case of eye contact, immediately flush eyes with water. Wash hands at shift end and prior to eating. CAUTION: Traces of polyetrafluoroethylene found to cause polymer fever and other hazardous decomposition products may be generated at high temperatures. Such high temperatures may require the use of increased ventilation and/or use of a NIOSH/MSHA-approved respirator. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses.

WARNING

Grease, Item 144, is combustible. Keep away from heat, sparks, and flames. Do not apply to hot surfaces; toxic gases may be released. Keep grease off skin, eyes, clothes. Prolonged or repeated contact may irritate the eyes and skin. Long-term use without hand protection may cause dermatitis. Wash hands thoroughly before eating, drinking, and smoking. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses, oil-resistant gloves, other protective clothing as needed.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
1254

WARNING

Grease, Item 145, is combustible. Keep away from heat, sparks, and flames. Do not apply to hot surfaces; toxic gases may be released. Do not breathe vapors. Keep grease off skin, eyes, and clothes. Prolonged or repeated contact may irritate the eyes and skin. Long-term use without hand protection may cause dermatitis. Wash hands thoroughly before eating, drinking, and smoking. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses, oil-resistant gloves, other protective clothing as needed, good ventilation.

WARNING

Grease, Item 146, is combustible. Keep away from heat, sparks, and flames. Do not apply to hot surfaces; toxic gases may be released. Keep grease off skin, eyes, clothes. Prolonged or repeated contact may irritate the eyes and skin. Long-term use without hand protection may cause dermatitis. Wash hands thoroughly before eating, drinking, and smoking. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses, oil-resistant gloves, other protective clothing as needed.

WARNING

Grease, Item 147, is a skin and eye irritant. Minimize contact with grease. Prolonged or repeated contact may irritate the eyes and skin. Long-term use without hand protection may cause dermatitis. Product used under normal conditions poses minimal hazard by inhalation. However, vapors produced during high temperature operations may cause headache, dizziness, and upper respiratory irritation. Wash hands thoroughly before eating, drinking, and smoking. Refer to the Material Safety Data Sheet (MSDS) for additional health and safety information. Protection: safety glasses, oil-resistant gloves, other protective clothing as needed, good ventilation.

WARNING

Grease, Item 148, may irritate the eyes and skin. Minimize contact with grease. Long-term use without hand protection may cause dermatitis. Product used under normal conditions poses minimal hazard by inhalation. Wash hands thoroughly before eating, drinking, and smoking. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses, oil-resistant gloves, other protective clothing as needed.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
1155

WARNING

Grease, Item 149, is combustible. Keep away from heat, sparks, and flames. Do not apply to hot surfaces; toxic gases may be released. Keep grease off skin, eyes, and clothes. Prolonged or repeated contact may irritate the eyes and skin. Long-term use without hand protection may cause dermatitis. Wash hands thoroughly before eating, drinking, and smoking. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses, oil-resistant gloves, other protective clothing as needed.

WARNING

Grease, Item 150, is a skin and eye irritant. Avoid any skin contact with grease/lubricant material. Prolonged or repeated contact may irritate the eyes and skin. Breathing vapor may irritate the upper respiratory tract. If swallowed, do not induce vomiting; aspiration may damage the lungs. Wash hands thoroughly prior to eating, drinking, or smoking. Do not apply to hot surfaces; toxic gases may be released. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Grease, Item 151, may cause moderate eye irritation. Prolonged or repeated skin contact may cause skin irritation. May cause dermatitis after prolonged contact. Keep grease away from ignition sources (heat, sparks, flame) and strong oxidizers. Store out of direct sunlight in a cool, dry, well-ventilated areas. In case of eye contact flush with water for at least 15 minutes and obtain medical attention. In case of skin contact wash area thoroughly with soap and water. If irritation persists seek medical attention. If inhaled, remove to fresh air, administer oxygen if required, and obtain immediate medical attention. If ingested, obtain immediate medical attention. Do not induce vomiting. Wash with soap and water after handling product. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles or face shields, approved gloves, good ventilation.

WARNING

Grease, Item 151A, is a skin and eye irritant. Avoid any skin contact with grease/lubricant material. Prolonged or repeated contact may irritate the skin; direct contact may irritate the eyes. Inhaling high concentrations of mists or vapors from heated product may cause headache, dizziness, and respiratory irritation. Keep containers closed when not in use. Do not use near heat, sparks, or hot surfaces; toxic gases may be released. Wash hands thoroughly prior to eating, drinking, or smoking. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
2156

WARNING

Hydraulic fluid, Item 154, is combustible. Do not use or store near flames, sparks, or hot surfaces. Use only in a well-ventilated area. If hydraulic fluid is decomposed by heat, toxic gases are released. Prolonged contact with liquid or mist can cause dermatitis and severe skin irritation. If there is any prolonged contact with skin, wash contacted area with soap and water. Remove contaminated clothing and launder before reuse. If liquid contacts eyes, flush eyes with water immediately. If fluid is swallowed, do not try to vomit; fluid may enter the lungs and cause severe injury. Get immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: rubber gloves, impervious protective clothing, NIOSH/MSHA-approved respirator, if prolonged contact with mist is likely.

WARNING

Hydraulic fluid, Item 155, if decomposed by heat, will release toxic gases. Inhalation of vapors should be avoided. Prolonged contact with liquid or mist can cause dermatitis and irritation. If there is any prolonged contact with skin, wash contacted area with soap and water. If liquid contacts eyes, flush eyes with water immediately for 15 minutes. Remove saturated clothing. If fluid is swallowed, do not induce vomiting. Get immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: rubber gloves.

WARNING

Insulating compound, Item 157, is flammable. Keep it away from ignition sources (heat, flame). Bond/ground metal containers during mixing or transfer to prevent ignition from static discharge. Keep compound off skin, eyes, and clothes. Direct contact may severely irritate the eyes. May irritate the skin. May cause allergic skin rash in sensitized individuals. Breathing vapor may cause headaches, dizziness, nausea, and respiratory irritation (marked by sore throat, chest discomfort, and difficulty in breathing). Certain individuals may develop "isocyanate sensitization", which will cause them to experience an "asthmatic-type" reaction at levels well below established limits. Long-term overexposure may cause permanent damage to brain, nervous system, kidneys, and lungs. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, neoprene gloves, forced ventilation, NIOSH/MSHA-approved respirator, if vapor exceeds established exposure limits.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
1157

WARNING

Insulating compound, Item 158, as an uncured product may irritate the eyes, skin, nose, and throat. Product releases toxic, irritating acetic acid during application and curing; mechanical ventilation should be used to keep acetic acid mist well below established exposure limits. Keep sealant off skin, eyes, and clothes. Keep sparks, flames, and heat away. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or goggles, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Lacquer, Item 182B, is flammable. Keep away from ignition sources such as heat, spark, and flames. Bond/ground metallic containers during use or transfer. Avoid contact; product may cause moderate to severe eye and skin irritation. In case of eye contact, flush eyes immediately with water for 15 minutes. If product contacts the skin, wash affected areas thoroughly with soap and water. Remove contaminated clothing immediately and launder before reuse. Avoid breathing vapors; inhalation may cause headache, dizziness, nausea, and respiratory irritation. Seek fresh air and possible medical attention if such symptoms persists. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Lacquer, Item 182C, is flammable. Keep away from potential sources of ignition, including heat, spark, and flame. Bond and ground metal containers to prevent ignition through static electrical discharge. Keep containers tightly closed, in a cool, dry area when not in use. Avoid contact. Direct contact may irritate the eyes and skin, particularly when prolonged or repeated. Avoid breathing vapors and mists. Inhalation may cause headache, dizziness, nausea, and respiratory irritation. In case of contact, flush affected areas immediately with water. Seek medical attention if irritation persists. NOTE: Covers a series of acrylic-nitrocellulose camouflage lacquers, ranging in color specification. May contain components that may, upon long-term use without proper protective equipment, cause nervous system damage, cancer, and reproductive effects. Certain components may be absorbed through the skin in levels that may affect inner organs. Products meeting this specification may have varying component ingredients. Product hazards vary with respect to unique chemical composition. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles; approved gloves; full-body protective clothing; NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
2258

WARNING

Lacquer, Item 183, Item 184, and Item 185, is flammable. Keep away from potential sources of ignition, including heat, spark, and flame. Bond and ground metal containers to prevent ignition through static electrical discharge. Keep containers tightly closed, in a cool, dry area when not in use. Avoid contact. Direct contact may irritate the eyes and skin, particularly when prolonged or repeated. Avoid breathing vapors and mists. Inhalation may cause headache, dizziness, nausea, and respiratory irritation. In case of contact, flush affected areas immediately with water. Seek medical attention if irritation persists. NOTE: Covers a series of acrylic-nitrocellulose camouflage lacquers, ranging in color specification. May contain components that may, upon long-term use without proper protective equipment, cause nervous system damage, cancer, and reproductive effects. Certain components may be absorbed through the skin in levels that may affect inner organs. Products meeting this specification may have varying component ingredients. Product hazards vary with respect to unique chemical composition. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles; approved gloves, full-body protective clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Lacquer, Item 186, Item 187, and Item 188, is flammable. Keep away from ignition sources such as heat, spark, and flames. Bond/ground metallic containers during use or transfer. Avoid contact; product may cause moderate to severe eye and skin irritation. In case of eye contact, flush eyes immediately with water for 15 minutes. If product contacts the skin, wash affected areas thoroughly with soap and water. Remove contaminated clothing immediately and launder before reuse. Avoid breathing vapors; inhalation may cause headache, dizziness, nausea, and respiratory irritation. Seek fresh air and possible medical attention if such symptoms persists. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Leak detection fluid, Item 189, is a mild skin and eye irritant. If eye contact occurs, flush with water. If eye irritation persists, seek medical attention. Wash hands with soap and water after use. If ingested, induce vomiting and seek medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses, approved gloves.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
1159

WARNING

Lubricant, Item 200, if applied to hot surfaces, will release toxic gases. Avoid contact with lubricant material. Direct eye contact and prolonged or repeated skin contact may cause mild irritation. Heavy mists or vapors generated by high temperatures may cause headache, dizziness, and respiratory irritation. Wash hands thoroughly prior to eating, drinking, or smoking. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or goggles, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Solid film lubricant, Item 201, is flammable. At high temperatures, it can decompose into a toxic substance. Keep container closed; keep sparks, flames, and heat away. Keep solid film lubricant off skin, eyes, and clothes. May irritate the eyes and skin. Do not breathe vapors. Breathing mists may cause headache, dizziness, nausea, respiratory irritation. Methylene chloride, a major component, has been found to cause cancer. May contain chemicals found to cause target organ and reproductive effects upon chronic overexposure. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, neoprene gloves, impervious clothing, forced ventilation, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Lubricating oil, Item 202, is combustible. Keep away from potential sources of ignition, such as heat, spark, and flame. Keep containers securely closed when not in use. Prolonged or repeated contact may irritate the skin. Liquid or vapor may irritate the eyes. Inhaling product vapors may cause headache, dizziness, nausea, and respiratory irritation. Product contains components that may be absorbed through the skin, thus contributing to the overall effects of overexposure to the product. Prolonged overexposure to product without proper personal protective equipment may cause cancer. Flush eyes thoroughly with water for at least 15 minutes. If ingested, provide water and seek medical attention. Wipe excess product from skin, then wash thoroughly with soap and water. Seek medical attention if irritation persists. If overcome by product vapor or mist, seek fresh air and possible medical assistance. Launder soiled clothing after use. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, approved gloves, full-body protective clothing, NIOSH/MSHA-approved respiratory protection, if vapors exceed established exposure limits.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
3160

WARNING

Lubricating oil, Item 203, may irritate the eyes and skin if prolonged or repeated contact occurs. If contact with skin is prolonged, wash area with soap and water. If product contacts eyes, flush eyes with water immediately. Remove and launder saturated clothing. Caution: Traces of benzene, found to cause cancer, may be generated at high temperatures. Such high temperature operations may require the use of increased ventilation and/or use of a NIOSH/MSHA-approved respirator. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses, approved gloves.

WARNING

Lubricating oil, Item 204A, may irritate skin if prolonged or repeated contact occurs. Liquid or mist may irritate the eyes. If liquid contacts eyes flush eyes with water immediately. Long-term exposure without proper hand protection may cause dermatitis. If there is any prolonged contact with skin, wash contacted area with soap and water. Remove saturated clothing. Breathing vapors generated at high temperatures or mists may cause headache, dizziness, and respiratory irritation. If fluid is swallowed, do not try to vomit; fluid may be aspired into lungs, causing damage. Get immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, NIOSH/MSHA-approved respirator, if oil mists exceed established exposure limits.

WARNING

Lubricating oil, Item 205, may irritate the eyes and skin if prolonged or repeated contact occurs. Long-term use without hand protection may cause dermatitis. Breathing mists may cause respiratory irritation. If there is any prolonged contact with skin, wash area with soap and water. Remove saturated clothing. If solution contacts eyes, flush eyes with water immediately. If oil is swallowed, do not try to vomit; aspiration may damage lungs. Get immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, NIOSH/MSHA-approved respirator, if oil mists exceed established exposure limits.

WARNING

Lubricating oil, Item 205A, may irritate the eyes and skin if prolonged or repeated contact occurs. Long-term use without hand protection may cause dermatitis. Breathing mists may cause respiratory irritation. If there is any prolonged contact with skin, wash area with soap and water. Remove saturated clothing. If solution contacts eyes, flush eyes with water immediately. If oil is swallowed, do not try to vomit; aspiration may damage lungs. Get immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, NIOSH/MSHA-approved respirator, if oil mists exceed established exposure limits.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
1262

WARNING

Lubricating oil, Item 206, may irritate the eyes and skin if prolonged or repeated contact occurs. If there is any prolonged contact with skin, wash area with soap and water. If solution contacts eyes, flush eyes with water immediately. Remove saturated clothing. Breathing vapor may irritate the upper respiratory tract. If oil is swallowed, do not try to vomit, aspiration may damage the lungs. Get immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, NIOSH/MSHA-approved respirator, if oil mists exceed established exposure limits.

WARNING

Lubricating oil, Item 207, may irritate the eyes and skin if prolonged or repeated contact occurs. Long-term use without hand protection may cause dermatitis. Breathing mists may cause respiratory irritation. If there is any prolonged contact with skin, wash area with soap and water. Remove saturated clothing. If solution contacts eyes, flush eyes with water immediately. If oil is swallowed, do not try to vomit; aspiration may damage lungs. Get immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, NIOSH/MSHA-approved respirator, if oil mists exceed established exposure limits.

WARNING

Lubricating oil, Item 208, may irritate the eyes and skin if prolonged or repeated contact occurs. Long-term use without hand protection may cause dermatitis. Breathing mists may cause respiratory irritation. If there is any prolonged contact with skin, wash area with soap and water. Remove saturated clothing. If solution contacts eyes, flush eyes with water immediately. If oil is swallowed, do not try to vomit; aspiration may damage lungs. Get immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, NIOSH/MSHA-approved respirator, if oil mists exceed established exposure limits.

WARNING

Lubricating oil, Item 209, is combustible. Keep away from ignition sources (heat, flame). Keep container closed. Keep lubricating oil off skin, eyes, and clothes. Direct contact may severely irritate the eyes. Prolonged or repeated contact may irritate the skin. Do not breathe vapors. Breathing mists may cause headache, dizziness, nausea, and respiratory irritation. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, neoprene or polyvinyl gloves, impervious clothing, good ventilation, NIOSH/MSHA-approved respirator, if oil mists exceed established exposure limits.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército 162

WARNING

Methyl ethyl ketone, Item 217, is flammable. Do not use near open flames, near welding areas, or on hot surfaces. Do not smoke when using it, and do not use it where others are smoking. Contact with liquid or vapor can cause skin and eye irritation, dermatitis, and drowsiness. If there is any prolonged skin contact, wash contacted area with soap and water. Remove solvent-saturated clothing. If vapors cause drowsiness, move to fresh air. If irritation persists, get medical attention. Dispose of liquid-soaked rags in approved metal container. When storing, metal containers of solution must be grounded to maintain electrical continuity. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: when handling liquid at air-exhausted workbench, wear approved goggles and gloves; when handling liquid or liquid-soaked cloth in open unexhausted area, wear chemical splashproof goggles and approved gloves.

WARNING

Methyl isobutyl ketone, Item 218, is flammable, and irritating to eyes, skin, nose, and throat. Keep container closed; keep sparks, flames, and heat away. Keep methyl isobutyl ketone off skin, eyes, and clothes. Wash contacted skin with soap and water. If solvent contacts eyes, flush them with clean water and get immediate medical help. Do not breathe vapors. Breathing vapor or mists may cause headache, dizziness, and nausea. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, impervious gloves and clothing, good ventilation, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Molybdenum disulfide, Item 219, may irritate the eyes and skin if prolonged or repeated contact occurs. Avoid any skin contact with grease material. Breathing vapor may irritate the upper respiratory tract. If swallowed, do not induce vomiting, aspiration may damage the lungs. Wash hands thoroughly prior to eating, drinking, or smoking. Do not apply to hot surfaces; toxic gases may be released. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
1263

WARNING

Nitric acid, Item 220, is reactive. Keep away from organic or combustible materials (wood, paper). May react with metals to form flammable hydrogen gas. When mixing with water, always add acid to water not water to acid. Keep off eyes, skin, and clothes. It is corrosive. May severely irritate or burn the eyes and skin. Do not breathe mists. Inhalation may cause headache and nausea and severe respiratory irritation marked by coughing and labored breathing. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, full-body impervious clothing, NIOSH/ MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Nitrogen, Item 221, is a non-toxic inert gas that may displace the air used for breathing and cause asphyxiation. Use nitrogen in a well-ventilated area. Symptoms of oxygen deficiency may include dizziness, weakened speech, and loss of coordination. However, asphyxiation can occur without warning signs. A positive pressure air line with mask or self-contained breathing apparatus should be available for emergency use. Compressed gas cylinder must be stored upright and firmly secured. Valve protection caps must be used to protect stored cylinders. Empty and full cylinders must be segregated. Do not heat compressed gas cylinders to increase the discharge rate. Caution: Nitrogen in a liquid state can cause skin burns and frostbite. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: face shield, cryogenic gloves, full-body protective clothing, safety shoes.

WARNING

Heat resistant aluminum paint, Item 221A, is flammable. Keep product away from heat, sparks, and open flame. Keep containers tightly closed when not in use. Long-term contact may cause drying, cracking and irritation of the skin. May react with skin and cause rash, scaling or blistering. Overexposure to product without use of proper personal protective equipment may cause nervous system damage. If overcome by vapors remove to fresh air, and obtain medical attention. If skin contact occurs, flush with water. If eye contact occurs, flush immediately with large amounts of water and seek medical attention, if ingested, do not induce vomiting, keep person warm and get medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, protective gloves, NIOSH/ OSHA-approved respiratory protection.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
11 69

WARNING

Polyurethane paint, Item 222, Item 222A, Item 223, Item 224, Item 225, Item 226, Item 227, and Item 227A, is flammable. Keep container closed; keep away from ignition sources (sparks, flames, heat). Bond and ground metal containers during transfer to prevent ignition through static discharge. Keep off eyes, skin, and clothes. May irritate the eyes and skin. May cause allergic skin reactions in sensitive individuals. Avoid breathing vapor. Inhalation may cause headache, dizziness, and respiratory irritation. Prolonged exposure may cause "asthmatic-type" reactions. Certain individuals may develop "sensitization", causing them to react adversely to vapor levels well below established exposure limits. Long-term overexposure to some solvents has been linked to brain and nervous system damage. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, long sleeve and long leg clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Polyurethane paint, Item 228, is flammable. Do not use near open flames, welding areas, or on hot surfaces. Bond/ground metal containers during mixing or transfer to prevent ignition through static discharge. Do not eat, drink, or smoke where paints are being mixed, handled, or cleaned up. Contains isocyanate compounds. Certain individuals may develop isocyanate sensitization, which will cause them to experience an asthmatic-type reaction at levels well below established limits. Avoid prolonged skin contact. After use, wash hands before eating or smoking. Breathing vapor may cause headache, dizziness, nausea, respiratory irritation. Long-term overexposure may cause allergic skin response, and delayed effects involving the blood, gastrointestinal, nervous and reproductive systems. May contain chromates, which have been found to cause cancer. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, long sleeve and long leg clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Paint remover, Item 230, may severely irritate or burn the eyes and skin. Keep paint remover off skin, eyes, and clothes. May be absorbed through the skin in potentially dangerous levels that may affect inner organs. Avoid breathing vapor. Inhalation may cause headache, dizziness, and nausea. Long-term overexposure may injure the lungs, pancreas, liver, and kidney. Contains components found to cause cancer. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, neoprene gloves, full-body protective clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits. Gloves should be changed frequently.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
165

WARNING

Paint remover, Item 231, is combustible. Use paint remover only with adequate ventilation. Do not use it near welding area, near open flame, or on hot surfaces. Corrosive: Contact may cause severe burns on exposed tissue. If spilled on clothing, change immediately; wash clothes before wearing again. Do not breathe vapors. Breathing vapor may cause headache, dizziness, nausea, respiratory irritation. Frequent replacement of gloves during stripping operations may be necessary. May contain chemicals that may be absorbed through the skin in potentially dangerous amounts that could affect inner organ systems. Chronic overexposure to certain chemicals may cause liver and kidney damage, and cancer. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles and face shield to protect the skin from contact, approved neoprene or polyvinyl gloves, apron, boots, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Parting compound, Item 233, is extremely flammable. Do not use near open flames, near welding areas, or on hot surfaces. Do not smoke when using it and do not use it where others are smoking. Bond/ground metal containers to prevent ignition of product vapors through static discharge. Dispose of liquid soaked rags in approved metal safety container. Avoid contact. Direct contact may severely irritate or burn the eyes. May irritate the skin, particularly upon prolonged or repeated contact. Inhaling product vapors may cause headache, dizziness, nausea, and irregular heart beat. Long-term overexposure without proper protective equipment may cause liver, kidney, and nervous system damage, and blood defects. FIRST AID: If product contacts eyes, flush eyes thoroughly with lukewarm water for 15 minutes; seek immediate medical attention. CONTAINS: Methylene Chloride (found to cause cancer), Propane, Isobutane. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles or face shield, approved gloves, protective clothing, NIOSH/MSHA-approved respiratory protection (air-supplied), if product vapor levels exceed established exposure limits.

WARNING

Petrolatum, Item 234, may irritate the eyes and skin if prolonged or repeated contact occurs. Use in a well-ventilated area. Avoid eye and skin contact. Do not breathe vapors. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, full-body protective clothing, NIOSH/MSHA-approved respirator, if oil mists exceed established exposure limits.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
1166

WARNING

Polyurethane coating, Item 240, is flammable. Keep container closed; keep away from ignition sources (sparks, flames, heat). Bond and ground metal containers during transfer to prevent ignition through static discharge. Keep off eyes, skin, and clothes. May irritate the eyes and skin. May cause allergic skin reactions in sensitive individuals. Avoid breathing vapor. Inhalation may cause headache, dizziness, and respiratory irritation. Prolonged exposure may cause "asthmatic-type" reactions. Certain individuals may develop "sensitization", causing them to react adversely to vapor levels well below established exposure limits. Long-term overexposure to some solvents has been linked to brain and nervous system damage. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, long sleeve and long leg clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Polyurethane coating, Item 240A, is flammable. Keep polyurethane coating away from potential sources of ignition, including heat, spark, and open flame. Store containers in a cool, dry area when not in use. Bond and ground metal containers to prevent ignition through static electrical discharge. Avoid eye and skin contact. Direct contact may cause moderate to severe irritation, particularly with prolonged or repeated use. Certain components may be absorbed through the skin in potentially dangerous levels that may affect inner organs. May cause skin sensitization, whereby exposure to minimal amounts of product result in allergic skin reactions. Avoid breathing vapors or mists. Inhalation may cause headache, dizziness, nausea and respiratory irritation. May trigger immediate or delayed "asthmatic-type" reactions. In case of contact, flush affected area immediately with plenty of water. Seek medical attention if irritation persists. Seek fresh air and medical attention if allergic reactions occur. Product may contain chemicals that may damage internal "target" organs upon long-term overexposure without proper personal protective equipment. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: approved gloves; safety goggles, full-body protective clothing; NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército 1267

WARNING

Polyurethane coating, Item 241, is flammable. Do not use near open flames, welding areas, or on hot surfaces. Bond/ground metal containers during mixing or transfer to prevent ignition through static discharge. Do not eat, drink, or smoke where paints are being mixed, handled, or cleaned up. Contains isocyanate compounds. Certain individuals may develop isocyanate sensitization, which will cause them to experience an asthmatic-type reaction at levels well below established limits. Avoid prolonged skin contact. After use, wash hands before eating or smoking. Breathing vapor may cause headache, dizziness, nausea, respiratory irritation. Long-term overexposure may cause allergic skin response, and delayed effects involving the blood, gastrointestinal, nervous and reproductive systems. May contain chromates, which have been found to cause cancer. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved protective gloves, long sleeve and long leg clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Primer, Item 254, is flammable. Keep container closed and store in a cool, dry place. Use only in well-ventilated areas. Bond and ground metal containers during use and transfer to prevent ignition through static discharge. Keep clear of all sources of ignition or sparks during application and curing. Breathing vapors may cause headaches, dizziness, confusion, and respiratory irritation. Long-term overexposure without protective equipment may cause liver and kidney damage, and may trigger "asthmatic-type" respiratory responses and allergic skin reactions. May cause skin and eye irritation. If skin or eye contact occurs, wash immediately with water for at least 15 minutes. If ingested, do not induce vomiting. Seek immediate medical attention. Wash hands thoroughly with soap and water after use. Launder contaminated clothing before reuse. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information Protection: safety glasses or goggles, approved gloves, and good ventilation, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Primer, Item 257 and Item 258, is flammable. Do not use near open flames, near welding areas, or on hot surfaces. Do not eat or smoke when using it, and do not use it where others are smoking. Contact with liquid or vapor can cause skin or eye irritation, dizziness, and headache. Prolonged overexposure can result in kidney and liver damage. After prolonged skin contact, wash contacted area with soap and water. Flush eyes for 15 minutes, seek medical attention. If vapors cause dizziness, go to fresh air. If irritation persists, get medical attention. Dispose of liquid-soaked rags in approved metal container. Contains zinc chromates which are listed as carcinogens under OSHA. Follow approved toxic waste disposal procedures. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: when handling small quantities (less than 1 gallon), wear eye protection, approved gloves, and apron; when handling large quantities of liquid, (greater than a gallon), at unexhausted workbench, wear approved goggles, gloves, apron, long sleeves, respirator.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
2268

WARNING

Primer coating, Item 259, is flammable - Keep away from ignition sources (heat, sparks, flame) and strong oxidizers. Store out of direct sunlight in cool, dry, well-ventilated non-confined areas; ventilation systems must be explosion-proof and grounded. Do not store above 120°F (49°C). Closed containers may explode when exposed to extreme heat. If cans rupture, extinguish all ignition sources and ventilate. May cause severe irritation to eyes. Prolonged contact without proper skin protection may cause pain, numbness and burns. Prolonged inhalation may cause respiratory irritation, temporary nervous system impairment. Overexposure may cause headache, dizziness, giddiness, and irritability. Ingestion may cause lung damage/death. Digestive system irritation with nausea, vomiting, nervous system impairment. In case of eye contact flush with large volumes of water for at least 15 minutes, obtain medical attention. In case of skin contact flush area thoroughly with soap and water. If irritation persists seek medical attention. If inhaled, remove to fresh air, obtain medical attention. If ingested, do not induce vomiting, obtain immediate medical attention. Wash with soap and water after handling product. Launder soiled clothing and rags after use. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles/face shields, full-body protective clothing, approved gloves, good ventilation, NIOSH/MSHA-approved respirator, if airborne levels exceed established exposure limits.

WARNING

Sealing compound, Item 272, may irritate skin or produce allergic skin reactions and "asthmatic-type" respiratory responses in susceptible individuals if prolonged or repeated contact occurs; effects may be delayed. May be absorbed through the skin in levels that may affect inner organ systems. Direct eye contact may cause severe irritation. In case of skin contact, wash area thoroughly with soap and water; if eye contact occurs, flush immediately with water for at least 15 minutes. Seek immediate medical attention. Use with proper ventilation. Vapors may irritate the nose and throat. Long-term use without protective equipment may cause liver and kidney damage, blood changes, and reproductive disorders. Keep container closed in a cool, dry place. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, approved gloves, protective clothing to prevent skin contact, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
1169

WARNING

Sealing compound, Item 273 and Item 274, is combustible. Keep container closed and store in a cool, dry place. Use only in well-ventilated areas. Keep clear of all sources of ignition or sparks during application. Breathing vapors may cause headaches, dizziness, and nausea; avoid prolonged inhalation of vapors. May cause skin and eye irritation. If skin or eye contact occurs, wash immediately with water for at least 15 minutes. If ingested, do not induce vomiting. Seek immediate medical attention. Wash hands thoroughly with soap and water after use. Launder contaminated clothing before reuse. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or goggles, approved gloves, good ventilation, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Sealing compound, Item 275, may irritate the eyes and skin. Keep container closed; keep sparks, flames, and heat away. Keep sealing compound off skin, eyes, and clothes. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles or safety glasses, impervious gloves, good ventilation.

WARNING

Sealing compound, Item 276, Item 277, Item 278, Item 279, Item 280, Item 281, Item 282, and Item 283, is combustible - do not use near open flames, near welding areas, or on hot surfaces. Keep containers closed when not in use. Avoid contact with eyes and skin. Liquid may be irritating to eyes. Repeated or prolonged contact with skin may result in dermatitis. Inhalation of product vapors may cause headache, dizziness, nausea, and respiratory irritation. Vapor may be irritating to eyes. If ingested, do not induce vomiting; seek medical attention. If eye contact occurs, flush them in a continuous stream of water for at least fifteen minutes. Seek medical attention. In case of skin contact, wipe affected areas with water and wash with soap and water. If irritation persists, seek medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical goggles, approved gloves.

WARNING

Sealing compound, Item 284, is flammable. Do not use near open flames, welding areas, or on hot surfaces. Do not smoke when using or where others are smoking. Avoid skin contact. May irritate the eyes and skin. Breathing vapor may cause headache, dizziness, and nausea. Use respirator in confined areas. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: goggles or safety glasses, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército

WARNING

Sealing compound, Item 285 and Item 286, may irritate the eyes and skin if prolonged or repeated contact occurs. Avoid skin and eye contact with thread locking sealant. If any liquid contacts skin or eyes, immediately flush affected area thoroughly with water. Wash hands thoroughly after handling. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or goggles, protective rubber or plastic gloves.

WARNING

Sealing compound, Item 287 and Item 288, can irritate skin and cause burns. Avoid contact with skin, eyes, and clothing. In case of contact, immediately flush skin or eyes with water for at least 15 minutes. Get medical attention for eyes. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information.

WARNING

Sealing compound, Item 290 and Item 291, is a two part sealing compound mixture consisting of a base compound and an accelerant. The following warning summarizes health and physical hazards of the product as a mixture. Minimize contact. Prolonged or repeated contact may irritate the eyes and skin. Liquid or vapor may irritate the eyes. Inhaling product vapors may cause headache, dizziness, nausea, and narcosis. Product contains components that may be absorbed through the skin, thus contributing to the overall effects of overexposure to the product. Prolonged overexposure to product without proper personal protective equipment may cause muscular weakness, insomnia, and nervous system damage. Flush eyes thoroughly with water for at least 15 minutes. Wipe excess product from skin, then wash thoroughly with soap and water. Seek medical attention if irritation persists. If overcome by product vapor or mist, seek fresh air and possible medical assistance. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, approved gloves.

WARNING

Sealing compound, Item 292, can irritate skin and cause burns. Avoid contact with skin, eyes, and clothing. In case of contact, immediately flush skin or eyes with water for at least 15 minutes. Get medical attention for eyes. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército

WARNING

Sealing compound, Item 293A, may irritate the eyes and skin if prolonged or repeated contact occurs. Avoid skin and eye contact with thread locking sealant. If any liquid contacts skin or eyes, immediately flush affected area thoroughly with water. Wash hands thoroughly after handling. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or goggles, protective rubber or plastic gloves.

WARNING

Sealing compound, Item 295, is combustible. Keep sealing compound away from potential sources of ignition, such as heat, spark, and flame. Keep containers securely closed when not in use. Prolonged or repeated contact may irritate the skin. Liquid or vapor may irritate the eyes. Inhaling product vapors may cause headache, dizziness, nausea, and respiratory irritation. Product contains components that may be absorbed through the skin, thus contributing to the overall effects of overexposure to the product. Prolonged overexposure to dust of cured product without proper personal protective equipment may cause cancer. Flush eyes thoroughly with water for at least 15 minutes. If ingested, provide water and seek medical attention. Wipe excess product from skin, then wash thoroughly with soap and water. Seek medical attention if irritation persists. If overcome by product vapor or mist, seek fresh air and possible medical assistance. Launder soiled clothing after use. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, approved gloves, full-body protective clothing, NIOSH/MSHA-approved respiratory protection, if airborne levels exceed established exposure limits.

WARNING

Sealing compound, Item 295A, Parts A and B, are flammable. Part A - May irritate the eyes and skin. May cause allergic skin reaction in certain individuals. Breathing vapor may cause headache, dizziness, nausea, respiratory irritation. Long-term overexposure may affect the heart, liver, kidney, and blood. Part B - May irritate the eyes and skin. May cause allergic skin reaction. May be absorbed through the skin in potentially dangerous amounts that may affect inner organ systems. Breathing vapor may cause headache, dizziness, nausea, respiratory irritation. Long-term overexposure may affect the liver and kidney. Mixture Part A & B - Flammable - Keep away from ignition sources (heat, flame). Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, impervious gloves, full-body protective clothing, good ventilation, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

This document contains export-controlled information. See WARNING on first page.

1º Batalhão de Aviação do Exército 2172

WARNING

Sealing compound, Item 296 and Item 296A, is a skin and eye irritant. Adequate ventilation required during curing. Prolonged or repeated exposure may irritate the eyes and skin. If skin or eye contact occurs, wash immediately with water for at least 15 minutes. If ingested, seek immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or goggles, approved gloves.

WARNING

Sealing compound, Item 297, is flammable. Keep product away from potential ignition sources such as heat, spark, and flame. Bond/ground metal containers. Keep container closed. Direct contact may cause mild skin irritation and moderate to severe eye irritation. Inhalation of product vapor may cause headache, dizziness, and impaired motor coordination. Long-term overexposure without proper protective equipment may damage the liver. CAUTION: Product safety and health hazards may vary according to manufacturer and manufacturer product code, since different compositions can conform to the specification. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: splashproof goggles or safety glasses, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Sealing compound, Item 301A, is extremely flammable. Keep away from ignition sources (heat, sparks, flame) and strong oxidizers. Keep all containers closed in a cool, dry place when not in use. Use only in well-ventilated non-confined areas; ventilation systems must be explosion-proof and grounded. May irritate the eyes and skin. Prolonged contact without proper skin protection can cause dermatitis. Prolonged inhalation may cause headaches, dizziness, respiratory irritation, drowsiness and nausea. In case of eye contact, flush with water for at least 15 minutes and obtain medical attention. In case of skin contact, flush area thoroughly with soap and water. If irritation persists seek medical attention. If inhaled, remove to fresh air, obtain immediate medical attention. If ingested, obtain immediate medical attention. Wash with soap and water after handling product. Launder soiled clothing and rags after use. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles/face-shields, approved gloves, full-body protective clothing, good ventilation, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
1193

WARNING

Sealing compound, Item 302A, is a two component product consisting of an epoxy resin, Part A and hardener, Part B. The precautions for each should be observed when separate or mixed. Do not mix batches greater than 1 pound to prevent excessive heat build-up with the release of toxic gases. Part A - Contact: Direct contact with eyes causes irritation. Skin contact may cause irritation and allergic skin reaction. Harmful if inhaled. Harmful if swallowed. In case of eye contact, flush with water; obtain medical attention if irritation persists. In case of skin contact, wash with soap and water and obtain medical attention if irritation persists. If swallowed, dilute by giving two glasses of water, obtain medical attention. If inhaled, remove from area to fresh air get immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, approved gloves, protective clothing, good ventilation, NIOSH/MSHA-approved respirator. Part B - Product causes severe eye and skin burns. Contact: In case of eye contact, flush with water for 15 minutes while holding lids open and obtain medical attention. In case of skin contact, wash area with soap and water, remove contaminated clothing and obtain medical attention. If swallowed, dilute by giving two glasses of water, obtain medical attention. In case of inhalation, remove to fresh air and obtain medical attention. Wash with soap and water after handling product. Launder soiled clothing and rags after use. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, approved gloves, protective clothing, good ventilation, NIOSH/MSHA-approved respirator.

WARNING

Sealing compound primer, Item 304A, is combustible - do not use near open flames, near welding areas, or on hot surfaces. Keep containers closed when not in use. Avoid contact with eyes and skin. Liquid may be irritating to eyes. Repeated or prolonged contact with skin may result in dermatitis. Inhalation of product vapors may cause headache, dizziness, nausea, and respiratory irritation. Vapor may be irritating to eyes. If ingested, do not induce vomiting; seek medical attention. If eye contact occurs, flush them in a continuous stream of water for at least fifteen minutes. Seek medical attention. In case of skin contact, wipe affected areas with water and wash with soap and water. If irritation persists, seek medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical goggles, approved gloves.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército 1139

WARNING

Sealing compound, Item 305, and Item 306, is combustible - do not use near open flames, near welding areas, or on hot surfaces. Keep containers closed when not in use. Avoid contact with eyes and skin. Liquid may be irritating to eyes. Repeated or prolonged contact with skin may result in dermatitis. Inhalation of product vapors may cause headache, dizziness, nausea, and respiratory irritation. Vapor may be irritating to eyes. If ingested, do not induce vomiting; seek medical attention. If eye contact occurs, flush them in a continuous stream of water for at least fifteen minutes. Seek medical attention. In case of skin contact, wipe affected areas with water and wash with soap and water. If irritation persists, seek medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical goggles, approved gloves.

WARNING

Silicone compound, Item 309, may irritate the eyes, skin, nose, and throat if prolonged or repeated contact occurs. Keep sparks, flames, and heat away. Keep grease off skin, eyes, and clothes. Do not breathe vapors. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles or safety glasses, protective gloves, other protective clothing as needed, good ventilation.

WARNING

Toluene, Item 339, is flammable. Do not use solution near welding areas, near open flames, or on hot surfaces. Do not smoke, and do not use it where others are smoking. Dispose of liquid-soaked rags in approved metal container. Store solvent in approved and grounded metal safety container. Bond/ground metal containers during transfer to prevent ignition from static discharge. May severely irritate the eyes on contact. May irritate the skin. Repeated exposure can cause dermatitis, and temporary tingling sensation in fingers. If any liquid contacts skin, flush affected area thoroughly with water. Immediately remove solvent-saturated clothing. Breathing vapor may cause headache, dizziness, nausea. If these symptoms occur, seek fresh air. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical goggles, approved (PVA) polyvinyl alcohol gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
1175

WARNING

Trichloroethane, Item 341, may irritate the eyes and skin if prolonged or repeated contact occurs. Avoid contact. Skin irritation is heightened by liquid trapped against the skin from contaminated clothing. May be absorbed through the skin in levels that may affect inner organs. Long-term exposure without proper hand protection may result in dermatitis. After prolonged skin contact, wash affected area with soap and water. Remove contaminated clothing. Get medical attention. Avoid inhaling vapor. Breathing vapor may cause narcotic effects (headache, dizziness, and nausea); severe acute exposure may cause heart damage. If vapors cause irritation, go to fresh air. Dispose of liquid-soaked rags in approved metal container. No smoking in area. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, full-body impervious clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Trichloroethane, Item 342, may irritate the eyes and skin if prolonged or repeated contact occurs and may be heightened by liquid trapped against the skin from contaminated clothing. After prolonged skin contact, wash contacted area with soap and water. Remove contaminated clothing. Get medical attention for severe skin and eye irritation. May be absorbed through the skin in levels that may affect inner organ systems. Breathing vapor may cause narcotic effects (headache, dizziness, and nausea) heart damage (following severe acute exposure). If these symptoms occur, seek fresh air. Dispose of liquid-soaked rags in approved metal container. No eating, drinking, or smoking in area. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: goggles, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército 1156

D-1.4 Explanation of Columns.

a. Column (1) - Item Number.

NOTE

Expendable supplies and materials with no National Stock Number (NSN) listed may be purchased from the manufacturer indicated by the five-digit code.

b. Column (2) - National Stock Number. This is the NSN assigned to the item; use it to request or requisition the item.

c. Column (3) - Description. Indicates the Federal item name and, if required, a description to identify the item. The second line for each item indicates the part number. The last line for each item indicates the Commercial and Government Entity (CAGE) in parentheses, if applicable.

d. Column (4) - Unit of Measure (U/M) / Unit of Issue (U/I). Indicates the measure used in performing the actual maintenance function. This measure is expressed by a two- or three-character alphabetical abbreviation (e.g., ea, lb, pr, cyl, lbs). If the unit of measure differs from the unit of issue, requisition the lowest unit of issue that will satisfy your requirements.

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército

SECTION II EXPENDABLE AND DURABLE ITEMS LIST

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
1	9320-01-247-7735	Abrasion Resistant Tape SS9538-002 (CAGE 78286)	rl
1A	5350-00-246-0331	Abrasive Cloth ANSI B74.18, Type 1, Class 1, 40-Grit (CAGE 80204)	sh
2	5350-00-192-5047	Abrasive Cloth ANSI B74.18, Type 1, Class 1, 80-Grit (CAGE 80204)	sh
3	5350-00-161-9066	Abrasive Cloth ANSI B74.18, Type 1, Class 1, 100-Grit (CAGE 80204)	sh
4	5350-00-192-5050	Abrasive Cloth ANSI B74.18, Type 1, Class 1, 150-Grit (CAGE 80204)	sh
5	5350-00-192-9316	Abrasive Cloth ANSI B74.18, Type 1, Class 1, 220-Grit (CAGE 80204)	sh
6	5350-00-161-9715	Abrasive Cloth ANSI B74.18, Type 1, Class 1, 240-Grit (CAGE 80204)	sh
7	5350-00-229-3081	Abrasive Cloth ANSI B74.18, Type 1, Class 1, 280-Grit (CAGE 80204)	sh
8	5350-00-246-0330	Abrasive Cloth ANSI B74.18, Type 1, Class 1, 320-Grit (CAGE 80204)	sh
9	5350-00-271-5950	Abrasive Cloth ANSI B74.18, 30-, 40-, 60-, 80-, 100-, 120-Grit (Assorted Pack) (CAGE 80204)	sh

*** Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.**

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
9A	5350-00-856-5700	Abrasive Cloth ANSI B74.18, Type 1, Class 1, 400-Grit (CAGE 80204)	sh
10	5350-00-221-0872	Abrasive Cloth ANSI B74.18, No. 320 (CAGE 80204)	sh
11	5350-00-584-4660	Abrasive Cloth ANSI B74.18, No. 80 (CAGE 80204)	ea
12	5350-00-584-4653	Abrasive Cloth ANSI B74.18, No. 180 (CAGE 80204)	ea
13	5350-00-584-4654	Abrasive Cloth ANSI B74.18, No. 220 (CAGE 80204)	ea
14	5350-00-967-5089	Abrasive Mat A-A-58054, 280 - 400-Grit (CAGE 58536)	sh
14A	3460-01-289-1062	Abrasive Pad Scotch-Brite 7448 (CAGE 27293)	sh
15	5350-00-721-8115	Abrasive Paper ANSI B74.18, 120-Grit (CAGE 80204)	sh
16	5350-00-721-8116	Abrasive Paper ANSI B74.18, 150-Grit (CAGE 80204)	sh
17	5350-00-224-7209	Abrasive Paper ANSI B74.18, 220-Grit (CAGE 80204)	sh
17A	5350-00-224-7207	Abrasive Paper ANSI B74.18, 240-Grit (CAGE 80204)	sh
18	5350-00-224-7202	Abrasive Paper ANSI B74.18, 360-Grit (CAGE 80204)	sh
19	5350-00-221-0882	Abrasive Paper ANSI B74.18, 120-Grit (CAGE 80204)	sh

*** Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.**

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Viatura
TM 1-76-36-23
1179

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
20	5350-00-186-8819	Abrasive Paper ANSI B74.18, 220-Grit (CAGE 80204)	sh
21		Deleted (Refer to Item 1)	
22	5345-01-193-6709	Abrasive Wheel ST-90-ALO-382 (CAGE 08659)	ea
23		Deleted (Refer to Item 25A)	
*24	6810-00-275-1215	Acetic Acid A-A-55829 (CAGE 58536)	bt
*25	6810-00-184-4796	Acetone ASTM D 329 (CAGE 81346)	5 gal
*25A	6850-01-326-1607	Adhesion Promoter No. 86A (CAGE 52152)	pt
26		Deleted (Refer to Item 182B)	
27		Deleted (Refer to Item 182C)	
28		Deleted (Refer to Item 30)	
29		Deleted (Refer to Item 66H)	
*30	8040-01-419-8062	Adhesive Dapcotac 3300 (CAGE 58093)	kt
*31	8040-00-839-4919	Adhesive EC1099 (CAGE 76381)	qt
*32	8040-01-163-3481	Adhesive EA9309.3NA (CAGE 04347)	kt
33		Deleted (Refer to Item 32)	
*33A	8040-01-446-7381	Adhesive EA9359.3 (CAGE 05972)	kt
*34	8040-00-016-8662	Adhesive EA 934NA (CAGE 33564)	kt

*** Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.**

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
*35	8040-00-463-7042	Adhesive EA 956 (CAGE 33564)	kt
*36	8040-00-858-9799	Adhesive EC1099 (CAGE 76381)	kt
*37	8040-00-273-8717 8040-00-165-8614	Adhesive 1300L (CAGE 1A9T3)	pt qt
*38	8040-00-181-7548 8040-00-123-6954 8040-00-959-1854	Adhesive EC1751 A/B (CAGE 52152)	2 oz pt qt
*39	8040-00-152-0063	Adhesive EC2126 (CAGE 94960)	2 oz
*40	8040-00-180-6161	Adhesive EC2214 (CAGE 04963)	5 gal
*41	8040-00-145-0432	Adhesive EC2216 (CAGE 04963)	kt
*42	8040-00-390-7959	Adhesive EC847 (CAGE 04963)	qt
42A	8040-00-185-5631	Adhesive FM37 (CAGE 07542)	bx
42B		Adhesive KS0004 (KE4238/HD3475) (CAGE 04347)	kt
43	8040-00-849-5196	Adhesive MIL-A-81236 (CAGE 81349)	qt
43A	8040-00-530-4820	Adhesive 7526F (CAGE 65313)	pt
*44	8040-01-284-3984	Adhesive 380 (CAGE 05972)	oz

*** Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.**

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de
1283

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
*44A	8030-00-180-6222	Adhesive 60931 (CAGE 05972)	bt
44B	8040-01-090-9320	Adhesive 42061 (Loctite 420) (CAGE 05972)	pt
45	8040-01-339-6818	Adhesive Loctite Primer 704 (CAGE 05972)	gal
*46	8040-00-515-2250	Adhesive MMM-A-1617 (CAGE 81348)	qt
*47	8040-00-714-8223	Adhesive MMM-A-121 (CAGE 81348)	tu
*48	8040-00-152-0017 8040-00-152-0028	Adhesive MMM-A-132, Type 1, Class 3 (CAGE 81348)	2.5 oz 6 oz
*49	8040-00-266-7429	Adhesive Pliobond, No. 20 (CAGE 34897)	pt
50		Deleted (Refer to Item 105A)	
51	8040-00-526-1910	Adhesive PS18 (CAGE 95696)	kt
*52	8030-00-225-4548	Adhesive RTV102 (CAGE 01139)	ca
*53	8040-00-902-3871	Adhesive RTV106 (CAGE 01139)	kt
*54	8040-00-522-3429	Adhesive RTV118 (CAGE 01139)	kt
*55	8040-01-481-1516	Adhesive RTV133 (CAGE 01139)	ca

*** Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.**

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
2182

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
*56	8040-00-118-2695	Adhesive RTV162 (CAGE 01139)	kt
*57	8040-00-144-9774 8040-00-145-0020	Adhesive RTV3145 (CAGE 71984)	10.3 oz 3 oz
57A		Deleted (Refer to Item 66E)	
58	8040-01-146-2656	Adhesive SL-5 (CAGE 15674)	200 yd
*59	8040-01-203-1443	Adhesive A-A-3097, Type 1, Class 2 (CAGE 58536)	oz
*59A	8040-01-140-0954	Adhesive A-A-3097, Type II, Class 3 (CAGE 58536)	oz
*60	8040-01-160-9551	Adhesive Versilok 204/Accelerator 4 (CAGE 30676)	3 oz
*60A		Adhesive 3003505 (CAGE 30676)	10 oz
61		Deleted (Refer to Item 37)	
62		Deleted (Refer to Item 271A)	
63	8040-01-180-4988	Adhesive 416 (CAGE 05972)	bt
63A		Adhesive 1357 (3M ID 62-1368-8536-5) (CAGE 76381)	gal
*64	8040-01-170-3599	Adhesive Versilok 506/Accelerator 4 (CAGE 30676)	3 oz
64A		Adhesive Curing Accelerator 3004043 (CAGE 30676)	qt
65	8040-01-129-2559	Adhesive 82C18 (CAGE 56221)	pt

*** Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.**

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
TM 1-1520-236-23

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
*66	8040-01-355-6366	Adhesive EA 9203 (CAGE 33564)	gal
66A	8040-00-148-9849	Adhesive Epocast 50A (CAGE 99384)	kt
66B	8040-00-843-7873	Adhesive Epon 815 (CAGE 86961)	kt
66C	8040-01-046-2944	Adhesive 1210A/B (CAGE 99384)	kt
66D	8030-00-086-1505 8040-00-822-6430	Adhesive Epon 828 (CAGE 54527)	pt qt
*66E	8040-01-010-8758 8040-00-843-0802	Adhesive, Clear RTV732 (CAGE 71984)	10.3 oz 3 oz
66F		Adhesive Magnobond 6380 (CAGE 22121)	kt
66G	8040-00-084-4338	Adhesive Hardener 9615A (CAGE 02684)	kt
66H	8040-01-151-4258	Adhesive Primer Chemlok 7701 (CAGE 30676)	gal
*67	8040-00-065-6578	Adhesive Primer EC 1945 A/B (CAGE 04963)	qt
*68	8040-01-192-2491	Adhesive Primer EC-3917 (CAGE 04963)	qt
68A	8040-01-181-7201	Adhesive, Thermofit S-1009 (CAGE 06090)	kt
68B	8040-01-498-3919	Adhesive Primer 94 (CAGE 04963)	gal

*** Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.**

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
2384

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
69	7930-00-267-5588	Aircraft Wax MIL-W-18723 (CAGE 81349)	gal
*70	6810-00-577-4889	Alcohol, Denatured 27 CFR 21.35 (CAGE 0MUS3)	qt
71	6810-00-264-5906	Alcohol, Ethyl A-A-59282 (CAGE 58536)	pt
*72	6810-00-983-8551 6810-00-286-5435	Alcohol, Isopropyl TT-I-735 (CAGE 81348)	32 oz gal
*73	8030-00-779-4699	Alodine, Chemical MIL-C-5541, Kit-120 (CAGE 84063)	kt
73A	5920-01-520-6122	Aluminum Mesh Screen SS9615 (CAGE 78286)	sh
73B	8030-00-292-1102	Antiseize Compound A-A-59313 (CAGE 58536)	cn
*74	8030-00-597-5367	Antiseize Compound MIL-A-907 (CAGE 81439)	2.5 lbs
*75	8030-01-044-5034	Antiseize Compound AMS 2518 (CAGE 81343)	lb
*76	8030-00-087-8630	Antiseize Compound MIL-PRF-83483 (CAGE 81349)	lb
77	8030-00-889-5285	Antiseize Compound 8001 (CAGE 78976)	tu
78	6515-00-303-8250	Applicator GG-A-616 (CAGE 81348)	pkg
*79	9150-00-159-5012	Assembly Fluid Assembly Fluid 1 (CAGE 56385)	tu

*** Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.**

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
80	8135-00-282-0565	Barrier Material MIL-PRF-131 (CAGE 81349)	rl
80A	1680-01-337-2890	Breather Material Airweave N-10 (CAGE 53912)	rl
80B		BPS LifeGuard Repair Kit	kt
80C		BPS Non-Skid Top Coat Repair Kit	kt
81	8315-01-244-7225	Braid, Textile S8999-7 (CAGE 59364)	ea
82	5977-01-101-9857	Brush 287511 (CAGE 99932)	ea
83	7920-00-205-2401	Brush MIL-B-43871 (CAGE 81349)	ea
84	7920-00-514-2417	Brush, Acid A-A-289 (CAGE 58536)	ea
85	8070-00-224-8022	Brush, Artist H-B-118 (CAGE 81348)	ea
86	8020-00-263-3866	Brush, Paint H-B-420 (CAGE 81348)	6 ea
87	8530-00-290-2920	Brush, Tooth A-A-123 (CAGE 58536)	bx
87A	5999-00-280-3499	Cap, Electrical MS25274-2 (CAGE 96906)	10 ea
87B	6850-00-306-9596	Brush Plating Solution, Cadmium SPS 5070 (CAGE 11924)	cn
88		Deleted (Refer to Item 160C)	
89		Deleted (Refer to Item 64)	

*** Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.**

This document contains export-controlled information. See WARNING on first page.

Aviação do Exército 1286

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
90	8305-00-267-3015	Cheesecloth CCC-C-440 (CAGE 81348)	yd
*91	6810-00-264-6517	Chromium Trioxide, Technical A-A-55827 (CAGE 58536)	5 lb cn
*92	6850-00-181-7280	Cleaning Compound Actusol T776 (CAGE 72008)	55 gal
93	6850-00-527-2426	Cleaning Compound AMS 1640 (CAGE 81343)	5 gal
*94	6850-01-390-7811	Cleaning Compound MIL-PRF-87937 (CAGE 81349)	5 gal
95	6850-00-209-7947	Cleaning Compound O-C-1889 (CAGE 81348)	gal
96	6850-01-215-4776	Cleaning Compound Spray "Cleen" (CAGE 65290)	gal
97	6850-00-181-7115	Cleaning Compound T-WD 602 (CAGE 88559)	5 gal
97A	7930-01-306-8369	Cleaning Compound 13005 (CAGE 1Z575)	bt
98	6850-00-224-6663	Cleaning Compound, Solvent MIL-PRF-372 (CAGE 81349)	gal
*99	6850-00-105-3084	Cleaning Compound, Solvent CRC 2016 (CAGE Z2542)	cn
*99A	6850-01-371-8048 6850-01-375-5554 6850-01-375-5553 6850-01-375-5555	Cleaning Compound, Solvent Electron (CAGE 0WU71)	15 oz cn gal 6 gal 55 gal
*99B	6850-01-411-8815 6850-01-412-0026 6850-01-412-0028	Cleaning Compound, Solvent Positron (CAGE 0WU71)	gal 6 gal 55 gal

*** Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.**

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
TM 1-1520-236-23

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
*99C	6850-01-443-9519	Cleaning Compound, Solvent Shopmaster RC (CAGE 0YG51)	qt
*100	6850-01-248-9828	Cleaning Compound, Solvent MIL-PRF-85570 (CAGE 81349)	cn
*100A	6850-00-264-9038	Cleaning Compound, Solvent MIL-PRF-680 (CAGE 81348)	5 gal
101		Deleted (Refer to Item 97A)	
102	7920-00-044-9281	Cloth, Cleaning A-A-59323 (CAGE 58536)	bx
102A	7920-00-165-7195	Cloth, Cleaning A-A-59323 (CAGE 58536)	bx
102B	8305-01-100-9061	Cloth, Coated Fluorpeel No. 3 (CAGE 07512)	rl
103	8305-00-641-5603	Cloth, Coated MIL-C-8068 (CAGE 81349)	yd
104	8305-01-102-7912	Cloth, Nylon MIL-C-20696, Type 1, Class 3 (CAGE 81349)	yd
105	8305-00-082-6135	Cloth, Satin MIL-C-9084 (CAGE 81349)	yd
105A	8030-00-575-5985	Coating Compound PR-420 (CAGE 83574)	pt
*106	8030-00-082-2425	Coating Compound MIL-C-8514 (CAGE 81349)	kt
106A	6850-00-616-9019	Coating Compound, Black Oxide MIL-C-13924 (CAGE 81349)	50 lbs

*** Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.**

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército 1288

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
106B	8010-01-054-7229	Coating Kit, Rain Erosion Resisting M331/M201 (CAGE 30676)	kt
107		Deleted (Refer to Item 209A)	
*108	6850-00-656-1292	Corrosion Compound MIL-C-10578 (CAGE 81349)	5 gal
*108A	8030-01-386-3877	Corrosion Preventive Compound Fluid Film Liquid A (CAGE 0RA06)	gal
*108B	8030-01-381-7311	Corrosion Preventive Compound Fluid Film Liquid AR (CAGE 0RA06)	gal
*108C	8030-01-512-2416	Corrosion Preventive Compound AMS-M-3171, Type VI (CAGE 81343)	kt
*109	8030-00-244-1297	Corrosion Preventive Compound MIL-C-16173, Class 1, Grade 2 (CAGE 81349)	gal
*110	8030-00-062-6950 8030-00-231-2345 8030-00-244-1299	Corrosion Preventive Compound MIL-C-16173, Class 1, Grade 1 (CAGE 81349)	qt gal 5 gal
*111	8030-00-837-6557 8030-00-244-1296	Corrosion Preventive Compound MIL-C-16173, Class 1, Grade 3 (CAGE 81349)	pt gal
*112	8030-00-062-5866 8030-00-526-1605	Corrosion Preventive Compound MIL-C-16173, Class 1, Grade 4 (CAGE 81349)	gal 5 gal
*113	8030-01-041-1596	Corrosion Preventive Compound MIL-C-85054, Type 1 (CAGE 81349)	pt
113A	8030-01-347-0979	Corrosion Preventive Compound MIL-DTL-85054, Type 1, Class 134A (CAGE 81349)	cn
*114	8030-00-938-1947	Corrosion Preventive Compound MIL-C-81309, Type 2, Class 2 (CAGE 81349)	16 oz

*** Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.**

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército 1839

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
*115	8030-00-546-8637	Corrosion Preventive Compound MIL-C-81309, Type 3, Class 2 (CAGE 81349)	16 oz
*115A	8030-00-285-1570	Corrosion Preventive Compound MIL-C-11796, Class 3 (CAGE 81349)	35 lbs
*116	6850-00-926-5298	Corrosion Removing Compound MIL-C-10578 (CAGE 81349)	15 gal
116A	6850-00-550-5565	Corrosion Removing Compound A-A-59260 (CAGE 58536)	500 lbs
*117	8030-00-065-0957	Corrosion Resistant Coating MIL-C-5541, Class 3 Alodine 600 (CAGE 81439)	qt
*118	8030-00-142-9272 8030-00-811-3723 8030-00-823-8039	Corrosion Resistant Coating MIL-C-5541, Class 1A Alodine 1200S (CAGE 81349)	pt bt gal
*118A	8030-01-018-2838	Corrosion Resistant Coating MIL-C-5541 (CAGE 81349)	bt
119	8320-01-362-5829	Cotton Swabs 6003-0019 (CAGE 17794)	pkg
120	8030-00-839-1442	Curing Agent (CAGE 17794)	cn
*121	9150-00-269-8246	Damping Fluid DC200-100SCTK (CAGE 71984)	cn
121A	6810-00-995-4804	Diethylenetriamine A-A-59162 (CAGE 58536)	pt
121B		Deleted (Refer to Item 99C)	
122	7930-00-764-5066	Dishwashing Compound P-D-410 (CAGE 81348)	qt

*** Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.**

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
1190

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
123	6810-00-682-6867	Distilled Water ASTM D 1193 (CAGE 81346)	gal
123A	9150-01-528-5624	Dry Lubricant MS-122AD (CAGE 18598)	16 oz
*124	6850-00-274-5421 6850-00-285-8012	Dry-Cleaning Solvent MIL-PRF-680, Type 2 (CAGE 81348)	5 gal 55 gal
*125	6830-01-011-7848	Dry Ice BB-C-104 (CAGE 81348)	10 lb
125A	8010-01-030-7250	Epoxy Coating 17564-4B2 (CAGE 17564)	kt
126		Deleted (Refer to Item 221B)	
*126A	8010-01-419-1142	Epoxy Coating Kit MIL-PRF-22750 (CAGE 81349)	kt
126B	8010-01-416-6556	Epoxy Coating Kit MIL-PRF-23377 (CAGE 81349)	kt
127		Deleted (Refer to Item 302A)	
128		Deleted (Refer to Item 182A)	
129		Deleted (Refer to Item 66A)	
130		Deleted (Refer to Item 66B)	
131		Deleted (Refer to Item 302B)	
132		Deleted (Refer to Item 66C)	
133		Deleted (Refer to Item 66G)	
133A		Deleted (Refer to Item 66D)	
*134	8040-00-061-8303	Epoxy Patch Kit EPK 0151 (CAGE 04347)	kt
*134A	8010-01-218-7354	Epoxy Primer MIL-PRF-85582 (CAGE 81349)	kt

*** Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.**

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
1191

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
*135	8010-00-082-2450	Epoxy Primer Coating Kit MIL-PRF-23377 (CAGE 81349)	kt
135A	8010-00-264-8866	Epoxy Primer Coating Kit MIL-P-53030 (CAGE 81349)	kt
*136	6850-00-431-8662	Etching Solution Tetra-Etch (CAGE 17217)	cn
*137	6810-00-006-4205	Ethylene Glycol ASTM E 1119 (CAGE 81346)	gal
137A	8315-00-006-9835	Fastener Tape, Hook A-A-55126 (CAGE 58536)	yd
137B	8315-00-006-9836	Fastener Tape, Pile A-A-55126 (CAGE 58536)	yd
137C	8315-00-935-0505	Fastener Tape, Pile A-A-55126 (CAGE 58536)	yd
138	1615-01-126-9445	Fiberglass Repair Kit 70072-15001-011 (CAGE 78286)	ea
138A		Fiberglass Ski Repair Kit L20500-200 (CAGE 17564)	kt
139	4020-00-240-2142	Fibrous Cord A-A-55622 (CAGE 58536)	1200 ft rl
139A	8030-00-195-4831	Filler, Metal Surface Dent 01125 (CAGE 10054)	ea
139B		Deleted (Refer to Item 141A)	
140	8305-00-641-5606	Flannel Cloth CCC-C-458 (CAGE 81348)	yd

*** Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.**

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército 1192

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
141	8010-00-958-8147	Fluorescent Paint A-A-713, Color: No. 38905 (CAGE 81348)	pt
141A	4210-01-056-8343 4210-01-139-4972	Foam Liquid, Fire Extinguishing MIL-F-24385 (CAGE 81349)	5 gal
141B	1560-01-305-7909	Fuel Tank Parts Kit 052M001-501 (CAGE 59297)	kt
142	1560-01-305-7912	Fuel Tank Parts Kit 052M004-501 (CAGE 59297)	kt
*143	9150-01-040-1423	Grease FS-3451 (CAGE 71984)	3 oz tu
*144	9150-00-754-2595	Grease MIL-G-21164 (CAGE 81349)	1.75 lbs
*145	9150-00-985-7246 9150-00-985-7247 9150-00-985-7248	Grease MIL-PRF-23827 (CAGE 81349)	1.75 lbs 6.5 lbs 35 lbs
*146	9150-00-141-6770	Grease MIL-G-25013 (CAGE 81349)	1.75 lbs
*147	9150-00-616-9020	Grease MIL-G-25537 (CAGE 81349)	1.75 lbs
*148	9150-01-584-4299	Grease A-A-59173 (CAGE 58536)	oz
*149	9150-00-944-8953 9150-00-145-0268	Grease MIL-PRF-81322 (CAGE 81349)	1.75 lb cn 5 lb cn
*150	9150-00-408-9635	Grease MIL-G-81827 (CAGE 81349)	1.75 lb cn
*151	9150-01-018-8960	Grease AMS-G-4343 (CAGE 0U583)	ca

*** Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.**

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
4193

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
*151A	9150-00-663-1770	Grease 630AA (CAGE 73219)	6 lbs
151B	9150-01-444-2469	Grease AA-100 (CAGE 64856)	ca
152	5325-00-074-3301	Grommet, Nonmetallic MS21266-2N (CAGE 96906)	ea
152A	5325-00-926-1394	Grommet, Nonmetallic MS21266-3N (CAGE 96906)	ea
153	8520-00-527-9942	Hand Cleaner P-H-31, Type 1, Class 1 (CAGE 81348)	pt
*154	9150-00-252-6383 9150-00-223-4134	Hydraulic Fluid MIL-PRF-5606 (CAGE 81349)	qt gal
*155	9150-00-149-7432	Hydraulic Fluid MIL-PRF-83282 (CAGE 81349)	gal
155A	9150-00-698-2382	Hydraulic Fluid, Automatic Transmission Dexron II (CAGE 24617)	qt
156	7690-01-368-2663	Identification Marker HM200-300 (CAGE 94858)	pkg
*157	5970-01-029-7961	Insulating Compound MIL-I-46058 (CAGE 81349)	cn
*158	5970-01-100-4464	Insulating Compound RTV102 (CAGE 01139)	2.8 oz
159	5970-01-363-8394	Insulating Compound RTV-3140 (CAGE 71984)	qt
160	5970-00-900-9372	Insulating Varnish 1201 (CAGE 08000)	cn

*** Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.**

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército 1194

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
160A	5970-01-356-5954	Insulation Sleeving MIL-I-631 (CAGE 81349)	36 in
160B	5970-01-072-0014	Insulation Sleeving, Boot MS3117-11AC (CAGE 96906)	ea
160C	5970-00-484-2821	Insulation Sleeving, Electrical M23053/8-009-C (CAGE 81349)	ea
160D	5970-00-729-2966	Insulation Sleeving PVC105-11 (CAGE 81349)	in
161	5970-00-899-6651	Insulation Sleeving, Heat-Shrinkable M22129-02-N (CAGE 81349)	ft
162	5970-00-812-2969	Insulation Sleeving, Heat-Shrinkable M23053/5-104-0 (CAGE 81349)	ft
163	5957-01-088-0413	Insulation Sleeving, Heat-Shrinkable M23053/1-202-0 (CAGE 81349)	ft
164	5970-00-740-2971	Insulation Sleeving, Heat-Shrinkable M23053/5-107-9 (CAGE 81349)	ft
165	5970-00-983-7970	Insulation Sleeving, Heat-Shrinkable M23053/5-105-5 (CAGE 81349)	ft
166		Insulation Sleeving, Heat-Shrinkable M23053/16-75-5 (CAGE 81349)	ft
167	5970-00-787-2310	Insulation Sleeving, Heat-Shrinkable M23053/5-101-0 (CAGE 81349)	ft
168		Deleted (Refer to Item 162)	
169	5970-00-812-2967	Insulation Sleeving, Heat-Shrinkable M23053/5-108-0 (CAGE 81349)	ft
170		Deleted (Refer to Item 160A)	

*** Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.**

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército 1235

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
171	5970-00-221-5316	Insulation Sleeving, Heat-Shrinkable MIL-I-631 (CAGE 81349)	ft
172	5970-00-899-6660	Insulation Sleeving, Heat-Shrinkable M22129-20-N (CAGE 81349)	ft
173		Deleted (Refer to Item 219A)	
174		Deleted (Refer to Item 160B)	
175	5970-00-146-1122	Insulation Sleeving, Heat-Shrinkable SS7072G0125W010 (CAGE 78286)	ft
176		Deleted (Refer to Item 180)	
177	5970-00-812-2974	Insulation Sleeving, Heat-Shrinkable M23053/5-103-0 (CAGE 81349)	ft
178	5970-00-781-6832	Insulation Sleeving, Heat-Shrinkable M23053/5-114-0 (CAGE 81349)	ft
179	5970-01-158-3818	Insulation Sleeving, Heat-Shrinkable M23053/11-130-C (CAGE 81349)	ft
180	5970-01-028-6789	Insulation Sleeving, Heat-Shrinkable MS3109-11AC (CAGE 96906)	ft
181	5970-00-832-4298	Insulation Tape A-A-59474 (CAGE 58536)	rl
182	5970-00-881-3657	Insulation Tape MIL-I-15126 (CAGE 81349)	rl
182A	5970-00-226-9577	Insulating Compound, Electrical Epocast 4-H-A/946 (CAGE 99384)	kt
*182B	8010-01-042-4196	Lacquer MIL-L-46159 (CAGE 81349)	cn
*182C	8010-00-066-9430	Lacquer MIL-PRF-81352 (CAGE 81349)	gal

*** Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.**

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
1196

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
*183	8010-00-082-2479	Lacquer MIL-L-19538 Color: Black (CAGE 81349)	qt
*184	8010-00-527-2888	Lacquer MIL-L-19538 Color: Olive Drab (CAGE 81349)	gal
*185	8010-00-083-6588	Lacquer MIL-L-19538, Class 1, X34089 (CAGE 81349)	5 gal
*186	8010-00-083-6588	Lacquer MIL-L-46159 (CAGE 81349)	16 oz
*187	8010-01-016-1488	Lacquer MIL-L-46159, Type 1 Color: Olive Drab (CAGE 81349)	pt
*188	8010-01-042-4196	Lacquer MIL-L-46159, Type 2 Color: Olive Drab (CAGE 81349)	16 oz
*189	6850-00-935-4068	Leak Detection Fluid 372 (CAGE 03530)	4 oz
190	6640-00-290-0146	Litmus Paper MS36253-2 (CAGE 96906)	vial
191	6640-00-290-0147	Litmus Paper MS36253-1 (CAGE 96906)	vial
192		Deleted (Refer to Item 285 or Item 286)	
193	9525-00-221-2650	Lockwire MS20995C20 (CAGE 96906)	1 lb sp
194	9505-01-054-2676	Lockwire MS20995C32 (CAGE 96906)	1 lb sp

*** Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.**

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
194A	9505-01-499-6879	Lockwire MS20995C47 (CAGE 96906)	1 lb sp
195	9525-01-047-6455	Lockwire MS20995CY20 (CAGE 96906)	1 lb sp
196	9525-00-618-0257	Lockwire MS20995NC20 (CAGE 96906)	1 lb sp
197	9525-00-803-3044	Lockwire MS20995NC32 (CAGE 96906)	5 lb sp
198	9525-00-990-7799	Lockwire MS20995NC40 (CAGE 96906)	1 lb sp
199	9525-00-409-1866	Lockwire MS20995NC47 (CAGE 96906)	1 lb sp
199A		Deleted	
199B		Deleted (Refer to Item 123A)	
199C	9150-01-106-7078	Lubricant Molykote III (CAGE 94499)	cn
*200	2640-00-476-3144	Lubricant, Inner Tube MIL-C-5024 (CAGE 81349)	gal
200A	6850-01-441-2633	Lubricant, Seal L-001 (CAGE 04171)	tu
200B		Lubricant, Solid Film MIL-L-8937, Type II (CAGE 81349)	gal
*201	9150-01-260-2534	Lubricant, Solid Film MIL-L-23398 (CAGE 81349)	16 oz
201A		Deleted (Refer to Item 200A)	
201B	6850-01-260-8055	Lubricant, Water Displacing MIL-L-87177, Type I (CAGE 81349)	cn

*** Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.**

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
1298

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
*202	9150-00-263-3490	Lubricating Oil MIL-PRF-7870 (CAGE 81349)	cn
*203	9150-00-543-7220	Lubricating Oil DOD-L-25681 (CAGE 81349)	lb
204	9150-00-292-9687	Lubricating Oil MIL-PRF-14107 (CAGE 81349)	5 gal
*204A	9150-00-753-4937	Lubricating Oil SAE J 1899 (CAGE 81343)	55 gal
*205	9150-00-985-7099	Lubricating Oil MIL-PRF-23699 (See Note) (CAGE 81349)	qt
*205A	9150-01-311-5640	Lubricating Oil MIL-PRF-6085 (CAGE 81349)	qt
*206	9150-01-209-2684	Lubricating Oil DOD-L-85734 (CAGE 81349)	qt
*207	9150-00-273-2388	Lubricating Oil MIL-PRF-6081 (CAGE 81349)	qt
*208	9150-00-782-2627	Lubricating Oil MIL-PRF-7808 (CAGE 81349)	qt
*209	9150-00-231-6689	Lubricating Oil MIL-PRF-32033 (CAGE 81349)	qt
209A	9150-00-664-4449	Lubricating Oil, Refrigerant Compresser ED45263-106 (CAGE 64959)	gal
210		Deleted (Refer to Item 151A)	
211	7920-00-260-1279	Machinery Towel DDD-T-541 (CAGE 81348)	50 ea bx

*** Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.**

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
1295

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
211A	1560-00-450-3622	Maintenance Kit, Window A-A-52686 (CAGE 81349)	kt
211B		Deleted (Refer to Item 66F)	
211C	7520-00-043-3408	Marking Pen A-A-2778 (CAGE 58536)	ea
212	7510-00-266-6712	Masking Tape, 1-inch A-A-883 (CAGE 58536)	rl
213	7510-00-266-6709	Masking Tape, 1 ½-inches A-A-883 (CAGE 58536)	rl
214	7510-00-266-6710	Masking Tape, 2-inches A-A-883 (CAGE 58536)	rl
215	7510-00-266-6707	Masking Tape, 3-inches A-A-883 (CAGE 58536)	rl
216	9340-01-177-8572	Mat, Reinforcing, Fibrous 1659 (CAGE 95746)	50 yd rl
*217	6810-00-281-2785 6810-00-281-2762 6810-00-281-2763	Methyl Ethyl Ketone ASTM D 740 (CAGE 81346)	gal 5 gal 55 gal
*218	6810-00-180-5976 6810-00-281-2761	Methyl Isobutyl Ketone ASTM D 1153 (CAGE 81346)	5 gal 55 gal
*219	6810-00-264-6715	Molybdenum Disulfide AMS-M-7866 (CAGE 81343)	1 lb
219A	2925-00-497-4957	Neoprene Sleeve 10-30233 (CAGE 77820)	ft
*220	6810-00-222-9655 6810-00-237-2918	Nitric Acid A-A-59105 (CAGE 58536)	500 ml 80 oz

*** Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.**

This document contains export-controlled information. See WARNING on first page.

4º Batalhão de Aviação do Exército
fl. 1200

MINISTÉRIO DA DEFESA
EXÉRCITO BRASILEIRO
4º BATALHÃO DE AVIAÇÃO DO EXÉRCITO
ESQUADRÃO CORONEL RICARDO PAVANELLO

TERMO DE ENCERRAMENTO PARCIAL

PREGÃO ELETRÔNICO Nº 07/2023
(Processo Administrativo n° **64020.004690/2023-98**)

Em conformidade com o disposto no art. 18, caput, da Lei 14.133, de 1º de abril de 2021, encerro parcialmente o processo em questão.

O presente processo, até esta data, conta com 6 volumes:

-volume I: página 01 a 200;
-volume II: página 201 a 400;
-volume III: página 401 a 600;
-volume IV: página 601 a 800;
-volume V: página 801 a 1000;
-volume VI: página 1001 a 1200.

Todas as páginas encontram-se autuadas e numeradas.

Manaus-AM, 23 de fevereiro de 2024.

[redacted] SOUSA - Maj
Chefe da Seção de Aquisições, Licitações e Contratos